

Office 2016 Client Software License Management Tool

Usage

cscript ospp.vbs /Option:Value ComputerName User Password

ComputerName: Name of remote computer. If a computer name is not passed local computer is used.

User: Account with required privilege on remote computer.

Password: Password for the account. If a User account and password are not passed current credentials are used.

Value: Required for outlined options.

Global /Options	Description
/act	Activate installed Office product keys.
/inkey:value	Install a product key (replaces existing key) with user-provided product key. Value parameter applies.
/unpkey:value	Uninstall an installed product key with user-provided partial product key (as displayed by the /dstatus option). Value parameter applies.
/inslic:value	Install a license with user-provided path to the .xrm-ms license. Value parameter applies.
/dstatus	Display license information for installed product keys.
/dstatusall	Display license information for installed licenses.
/dhistoryacterr	Display MAK/Retail activation failure history.
/dinstid	Display installation ID for offline activation.
/actcid:value	Activate product with user-provided confirmation ID. Value parameter applies.
/rearm	Reset the licensing status for all installed Office product keys.
/rearm:value	Reset the licensing status for an Office license with user provided SKUID value (as displayed by the /dstatus option). Value parameter applies.
/ddescr:value	Display the description for a user-provided error code. Value parameter applies.
KMS client /Options	Description
/dhistorykms	Display KMS client activation history.
/dcmid	Display KMS client machine ID (CMID).
/sethst:value	Set a KMS host name with user-provided host name. Value parameter applies.
/setprt:value	Set a KMS port with user-provided port number. Value parameter applies.
/remhst	Remove KMS host name (sets port to default).
/cachst:value	Permit or deny KMS host caching. Value parameter applies (TRUE or FALSE).
/actype:value	Set volume activation type. Value parameter applies. (Windows 8 and above support only) Values: 1 (for AD) or 2 (for KMS) or 3 (for Token) or 0 (for all).
/skms-domain:value	Set the specific DNS domain in which all KMS SRV records can be found. This setting has no effect if the specific single KMS host is set via /sethst option. Value parameter applies. (Windows 8 and above support only) Value:FQDN
/ckms-domain	Clear the specific DNS domain in which all KMS SRV records can be found. The specific KMS host will be used if set via /sethst option. Otherwise default KMS auto-discovery will be used. (Windows 8 and above support only)
Token /Options	Description
/dtokils	Display installed token-based activation issuance licenses.
/rtokil:value	Uninstall an installed token-based activation issuance license with user-provided license id (as displayed by the /dtokils option). Value parameter applies.
/stokflag	Set token-based activation only flag. (Windows 7 support only)
/ctokflag	Clear token-based activation only flag. (Windows 7 support only)
/dtokcerts	Display token-based activation certificates.
/tokact:value1:value2	Token activate with a user-provided thumbprint (as displayed by the /dtokcerts option) and a user-provided PIN (optional). Value parameter applies.

Prior to running ospp.vbs ensure that:

Windows firewall allows WMI traffic on remote computer.

You have or pass credentials with required permissions on remote computer.

Cmd.exe is elevated (right click > Run as administrator).

Sample Usage

```
cscript ospp.vbs /act 'Activate Office on local computer.
```

```
cscript ospp.vbs /act mypc1 'Activate Office on remote computer mypc1 with current credentials.
```

```
cscript ospp.vbs /inkey:MFKXT-F6DT2-THMRV-KDWH2-TCDDTC 'Install an Office product key on local computer.
```

```
cscript ospp.vbs /inslic:\\myserver\licenses\tail.xrm-ms 'Install license on local computer.
```

```
cscript ospp.vbs /inslic:"\\myserver\work\licenses\office2016\tail.xrm-ms" mypc1 'Install license on remote computer mypc1. Note the path is enclosed in "" since the value contains spaces.
```

```
cscript ospp.vbs /ddescr:0xC004F009 'Display the description for error code.
```

```
cscript ospp.vbs /actype:1 'Set volume activation type to Active Directory only.
```

/Token only

```
cscript ospp.vbs /rtokil:4476b20e 'Uninstall an issuance license with license ID.
```

cscript ospp.vbs /tokact:96DE6755ABE0BC7D398E96C3AA3C7BFE8B565248 'Token activate with thumbprint.

cscript ospp.vbs /tokact:56AE6755AAB0BC7D398E96C3AA3C7BFE8B565256:54344 'Token activate with thumbprint & PIN.